

1. A flywheel assembly for a power transmission system for transmitting engine torque [to a driven unit], comprising:

5 an elastic plate secured to a crankshaft to rotate therewith;

a flywheel body secured to said elastic plate and having an engaging [engageable] surface for engaging with a clutch disc; and

10 a reinforcing member for reinforcing said elastic plate at a portion of said elastic plate which is secured to said crankshaft;

15 said elastic plate having an axial rigidity in the range of 600 kg/mm to 2200 kg/mm so as to ensure transmission of engine torque through said flywheel assembly [to said driven unit] while decreasing noise produced by a bending vibration of said crankshaft;

20 wherein each of said elastic plate, said flywheel body and said reinforcing member comprises a first portion, said first portion of said flywheel body being placed axially between said first portions of said elastic plate and said reinforcing member, and said first portions of said elastic plate, said flywheel body and said reinforcing member defining clearances for allowing said first portion of said flywheel body to move axially between said first portions of said elastic plate and said reinforcing member.

25

2. A flywheel assembly as set forth in claim 1, wherein said axial rigidity is in the range of 600 kg/mm to 1700 kg/mm.

30 3. A flywheel assembly as set forth in claim 2, wherein an axial run-out of said [engageable] surface when rotated by said crankshaft is no more than 0.1 mm.

F Engaging

4. A flywheel assembly according to claim 1, wherein  
 said reinforcing member (4) and said elastic plate (2) are  
 fastened to said crankshaft (1) by a fastening means (3), and  
 said elastic plate is clamped between said crankshaft and said  
 5 reinforcing member.

5. A flywheel assembly according to claim 4, wherein  
 said elastic plate is circular and comprises an outer peripheral  
 portion (2b) surrounding said first portion of said elastic plate,  
 10 so that said first portion of said elastic plate is an inner portion  
 of said elastic plate, said flywheel body comprises an outer  
 peripheral portion (5a) which surrounds said first portion of  
 said flywheel body, so that said first portion of said flywheel  
 body is an inner portion of said flywheel body, said outer  
 15 peripheral portions of said elastic plate and said flywheel body  
 are fastened together by a second fastening means (6), said  
 inner portion of said flywheel body comprises an inwardly  
 facing inside cylindrical surface defining a central circular hole  
 (5b), said reinforcing member comprises a cylindrical portion  
 20 (4a) which is received in said circular hole (5b) of said  
 flywheel body, and comprises an outwardly facing outside  
 cylindrical surface surrounded by said inwardly facing  
 cylindrical surface of said flywheel body, said first portion of  
 said reinforcing member is in the form of an outward flange  
 25 (4b), said first portion of said flywheel body is [slidably]  
 mounted on said cylindrical portion of said reinforcing member  
 [so that], and said cylindrical portion of said reinforcing  
member is sized to allow said first portion of said flywheel  
 body [is] to slide axially [slidable] between said inner portion  
 30 of said elastic plate and said outward flange of said reinforcing  
 member.

E2  
 Cont

F

6. A flywheel assembly according to claim 4, wherein said inner portion of said flywheel body comprises a first surface (5f) which is substantially parallel to said engaging [engageable] surface (5g) and <sup>which</sup> faces toward said elastic plate, and a second surface (5d) which is substantially parallel to said ~~engaging~~ <sup>engageable</sup> surface and which faces toward said outward flange of said reinforcing member, said inner portion of said elastic plate comprising an abutting surface confronting said first surface of said flywheel body and limiting an axial movement of said inner portion of said flywheel body [elastic plate] by abutting against said first surface of said flywheel body, said outward flange of said reinforcing member comprises an abutting surface confronting said second surface of said flywheel body and limiting the axial movement of said inner portion of said flywheel body by abutting against said second surface of said flywheel body, an axial distance between said first and second surfaces of said flywheel body is smaller than an axial distance between said abutting surfaces of said elastic member and said reinforcing member.

7. A flywheel assembly according to claim 6, wherein said second surface (5d) of said inner portion of said flywheel body is located axially between said first surface (5f) and said engaging [engageable] surface (5g) of said flywheel body.

8. A flywheel assembly for a power transmission system for transmitting engine torque [to a driven unit], comprising:

an elastic plate secured to a crankshaft to rotate therewith;

a flywheel body secured to said elastic plate and having an engaging [engageable] surface for engaging with a clutch

disc; and

a reinforcing member for reinforcing said elastic plate at a portion of said elastic plate which is secured to said crankshaft; and

5        said engaging [engageable] surface having an axial run-out which is equal to or less than 0.1 mm;

wherein each of said elastic plate, said flywheel body and said reinforcing member comprises a first portion, said first portion of said flywheel body being placed axially between said first portions of said elastic plate and said reinforcing member, and said first portions of said elastic plate, said flywheel body and said reinforcing member defining clearances for allowing said first portion of said flywheel body to move axially between said first portions of said elastic plate and said reinforcing member.

10

15

9. A flywheel assembly comprising:

a crankshaft [driving shaft] (1) for transmitting torque;

a circular elastic plate [member] (2) comprising an outer portion and an inner portion and extending radially inwardly from said outer portion to said inner portion, said inner portion of said elastic plate [member] being fastened to a shaft end of said crankshaft [driving shaft];

20

an annular flywheel body [member] (5) comprising an outer portion and an inner portion and extending radially inwardly from said outer portion to said inner portion of said flywheel body [member], said outer portion of said flywheel body [member] being fastened to said outer portion of said elastic plate [member], said inner portion of said flywheel body [member] comprising a central circular hole; and

25

30

a reinforcing member (4) comprising a cylindrical portion (4a) axially extending from a first member end to a

Q2  
cont

second member end, an inner portion extending radially inwardly from said first member end of said cylindrical portion, and an outward flange (4b) extending radially outwardly from said second member end of said cylindrical portion, said inner  
5 portion of said reinforcing member being fastened to said shaft end of said crankshaft [driving shaft], said cylindrical portion of said reinforcing member being fit in said circular hole of said flywheel body [member] with a clearance to form a loose fit;

10 wherein said inner portion of said elastic plate [member] is fixedly clamped between said shaft end of said crankshaft [driving shaft] and said inner portion of said reinforcing member, said inner portion of said flywheel body [member] is [loosely] fit over said cylindrical portion of said  
15 reinforcing member and located axially between said inner portion of said elastic plate [member] and said outward flange of said reinforcing member, said outward flange is axially spaced from said inner portion of said elastic plate [member] at an axial distance which allows axial movement of said inner  
20 portion of said flywheel body between said inner portion of said elastic plate [member] and said outward flange of said reinforcing member.

25 10. A flywheel assembly according to claim 9 [3], wherein said elastic plate [member] has an axial rigidity which is in the range of 600 kg/mm to 2200 kg/mm.

30 11. A flywheel assembly according to claim 9, wherein a wall thickness of said inner portion of said reinforcing member is greater than a wall thickness of each of said outward flange[s] of said reinforcing member and said inner portion of said elastic plate [member], said wall thickness of each of said

Q2  
Unit

inner portion and said outward flange of said reinforcing member and said inner portion of said elastic plate [member] being a dimension measured in an axial direction parallel to an axis of said crankshaft [driving shaft].

5

12. A flywheel assembly according to claim 9, further comprising a first fastening means for fastening said outer portions of said elastic plate [member] and said flywheel body [member] together, and a second fastening means for fastening said inner portions of said elastic plate [member] and said reinforcing member to said shaft end of said crankshaft [driving shaft], each of said first and second fastening means comprises screw fasteners extending axially along an axis of said crankshaft [driving shaft].

10

15

<sup>13</sup>  
16. A flywheel assembly for a power transmission system for transmitting engine torque, comprising:

a crankshaft;

an elastic plate comprising an inner portion secured to a shaft end of said crankshaft;

20

a flywheel body secured to said elastic plate and having an engaging surface for engaging with a clutch disc; and

a reinforcing member for reinforcing said elastic plate at said inner portion of said elastic plate;

25

wherein said elastic plate has an axial rigidity in the range of 600 kg/mm to 2200 kg/mm so as to ensure transmission of engine torque through said flywheel assembly, while decreasing noise produced by a bending vibration of said crankshaft; and

30

wherein said elastic plate is clamped axially between said reinforcing member and said shaft end of said crankshaft.

28. A flywheel assembly as set forth in claim 16,  
wherein an axial run-out of said engaging surface when rotated  
by said crankshaft is no more than 0.1 mm.

5

31. A flywheel assembly for a power transmission  
system for transmitting engine torque, comprising:

a crankshaft;

an elastic plate comprising an inner portion secured to  
a shaft end of said crankshaft;

10

a flywheel body secured to said elastic plate and having  
an engaging surface for engaging with a clutch disc; and

a reinforcing member for reinforcing said elastic plate  
at said inner portion of said elastic plate;

15

wherein said engaging surface has an axial run-out  
which is no more than 0.1 mm; and

wherein said elastic plate is clamped axially between  
said reinforcing member and said shaft end of said crankshaft.